

Column Diameter	Bottom Shaft Diameter	Top Shaft Diameter	Inside Shaft Diameter	Round Support Clearance	Square Support Clearance	Bead Width	Loss if cut at Bead	Tuscan Capital Support Ring	Minimum Thickness of Column Wall	Available Lengths
(Shown on graphic as)	( E )	( A )	( ID )			( D )	( B )	( C )		
8"	8"	7"	5-5/8"	5-1/8"	3-1/2"	1-3/8"	5-1/2"	2-11/16"	3/8"	8
8"	7-5/8"	6-5/8"	5-5/8"	5-1/8"	3-1/2"	7/8"	4-1/4"	-	3/8"	8,9,10,12
10"	10-1/8"	9-1/4"	7-1/2"	7"	4-7/8"	1-1/4"	6"	2-7/8"	3/8"	7
10"	10-1/8"	9-1/4"	7-1/2"	7"	4-7/8"	1-3/16"	7-5/8"	2-7/8"	3/8"	8
10"	10-1/16"	9"	7-1/2"	7"	4-7/8"	1-1/4"	5-7/8"	2-7/8"	3/8"	8,9
10"	9-1/4"	8-1/2"	7-1/2"	7"	4-7/8"	5/8"	5-1/2"	-	3/8"	8,9,10,12,14,16
12"	12-1/16"	10-1/8"	8-15/16"	8-7/16"	5-7/8"	7/8"	5-3/4"	3-5/16"	3/8"	8
12"	12"	10-1/16"	8-15/16"	8-7/16"	5-7/8"	7/8"	5-3/8"	3-1/2"	3/8"	8,9
12"	11-5/8"	10"	8-15/16"	8-7/16"	5-7/8"	1-5/16"	5-1/4"	3-1/2"	3/8"	8,9,10,12
14"	13-1/2"	11-5/8"	10-1/2"	10"	7"	1-11/16"	7-1/2"	3-11/16"	1/2"	8,9,10
14"	13-5/8"	11-3/4"	10-1/2"	10"	7"	1-1/8"	7-1/2"	4-5/16"	1/2"	8,9,10,12
16"	15-5/8"	13-7/16"	12-1/4"	11-3/4"	8-1/4"	1-1/4"	8"	4-3/4"	1/2"	8,9,10,12
16"	15-7/8"	13-1/2"	12-1/4"	11-3/4"	8-1/4"	1-1/2"	7-3/4"	4-3/4"	1/2"	8,9,10,12,14,16,18,20
18"	17-1/2"	15-1/4"	13-7/8"	13-3/8"	9-3/8"	1-3/8"	8-1/2"	5-3/16"	1/2"	8,9,10,12,14,16,18,20
20"	19-3/4"	17"	16"	15-1/2"	10-7/8"	2"	9-1/2"	5-1/2"	1/2"	8,9,10,12,14,16,18,22
24"	23-5/8"	19-3/4"	18-1/2"	18"	12-5/8"	2-1/2"	12-1/8"	7-5/16"	5/8"	8,9,10,12,14,16,18,22,24
36"	35-3/4"	29-3/4"	28"	27-1/2"	19-1/8"	2-1/2"	16"	10-1/2"	1"	8,9,10,12,14,16,18,22

