

Column Diameter	Bottom Shaft Diameter	Top Shaft Diameter	Inside Shaft Diameter	Round Support Clearance	Square Support Clearance	Capital Width	Capital Height	Abacus Height	Available Lengths
(Shown on graphic as)	(E)	(A)	(ID)			(X)	(Y)	(Z)	
22"	21-9/16"	18-3/8"	16"	15-3/4"	11-1/8"	27"	8-7/8"	4"	6
23"	22-13/16"	18-3/8"	16"	15-3/4"	11-1/8"	27"	8-7/8"	4"	8
24"	23-7/16"	18-3/8"	16"	15-3/4"	11-1/8"	27"	8-7/8"	4"	9
24"	24"	18-3/8"	16"	15-3/4"	11-1/8"	27"	8-7/8"	4"	10
25"	24-1/4"	21-1/8"	20"	19-3/4"	13-15/16"	30-5/8"	9-7/8"	4"	6
26"	25-1/2"	21-1/8"	20"	19-3/4"	13-15/16"	30-5/8"	9-7/8"	4"	8
26"	26-1/8"	21-1/8"	20"	19-3/4"	13-15/16"	30-5/8"	9-7/8"	4"	9
27"	26-11/16"	21-1/8"	20"	19-3/4"	13-15/16"	30-5/8"	9-7/8"	4"	10
28"	27-5/8"	21-1/8"	20"	19-3/4"	13-15/16"	30-5/8"	9-7/8"	4"	11.5
29"	28-3/16"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	8
29"	28-9/16"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	9
29"	28-7/8"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	10
30"	29-9/16"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	12
31"	30-3/16"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	14
31"	30-7/8"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	16
32"	31-9/16"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	18
32"	31-7/8"	25-7/8"	24"	23-3/4"	16-3/4"	37-7/8"	12-3/16"	5-5/8"	19

