

Column Width	Bottom Shaft Width	Top Shaft Width	Inside Shaft Width	Round Support Clearance	Square Support Clearance	Bead Width	Minimum Thickness of Column Wall	Available Lengths
(Shown on graphic as)	(E)	(A)	(ID)			(D)		
10"	9"	7-5/8"	6-1/2"	6"	4-1/8"	1-1/4"	1/2"	5' 6"
10"	9-5/8"	7-5/8"	6-1/2"	6"	4-1/8"	1-1/4"	1/2"	8'
10"	10-1/8"	7-5/8"	6-1/2"	6"	4-1/8"	1-1/4"	1/2"	10'
12"	11-3/8"	9-5/8"	8-1/2"	8"	5-5/8"	1-1/4"	1/2"	5' 6"
12"	12"	9-5/8"	8-1/2"	8"	5-5/8"	1-1/4"	1/2"	8'
14"	13-1/4"	9-5/8"	8-1/2"	8"	5-5/8"	1-1/4"	1/2"	12'
16"	13-5/8"	9-5/8"	8-1/4"	7-3/4"	5-3/8"	1-1/4"	5/8"	5'
16"	16"	9-5/8"	8-1/4"	7-3/4"	5-3/8"	1-1/4"	5/8"	8'
18"	17-19/32"	9-5/8"	8"	7-1/2"	5-1/8"	1-1/4"	3/4"	10'

